

## Ezeewin Smartcut Series

- Windows Based Operating CNC Software
- In Built programing Software
- 17" LCD Display
- 2 GB Program memory
- X,Y Axis AC Servo & U,V Axis - Stepper Servo
- Motorised Z Axis
- Auto Wire Tension Facility
- Equipped with wire guide system



### Technical Specifications

| Machine Specifications     | Smartcut 4032 Ci | Smartcut 5040 Ci | Smartcut 6350 Ci | Smartcut 8063 Ci | Smartcut 4032C | Smartcut 5040C | Smartcut 6350C C | Smartcut 8063C |
|----------------------------|------------------|------------------|------------------|------------------|----------------|----------------|------------------|----------------|
| X,Y Axis Travel (mm)       | 400 x 320        | 500 x 400        | 630 x 500        | 800 x 630        | 400 x 320      | 500 x 400      | 630 x 500        | 800 x 630      |
| Work Table Size (WxD mm)   | 600 x 380        | 720 x 460        | 820 x 550        | 1070 x 710       | 600 x 380      | 720 x 460      | 820 x 550        | 1070 x 710     |
| Job Admit (mm)             | 330              | 330              | 430              | 430              | 330            | 330            | 430              | 430            |
| Max. Workpiece Weight (Kg) | 450              | 600              | 800              | 1200             | 450            | 600            | 800              | 1200           |
| Max Taper Angle (Deg/mm)   | * +/- 3/100      | * +/- 3/100      | * +/- 3/100      | * +/- 3/100      | * +/- 3/100    | * +/- 3/100    | * +/- 3/100      | * +/- 3/100    |
| X,Y LM Guide               | YES              | YES              | YES              | YES              | YES            | YES            | YES              | YES            |

## Ezeewin Smartcut NXG Series

- Controller CNC System :Windows Based O.S.
- CNC Controller : 4 Axis Simultaneous with AUTOCUT CNC
- Screen Display : 17" LCD
- Min. Command Input (mm) :0.001
- Input Power Supply :Linear, Circular
- Average Power :2.5
- Consumption (KVA) :2
- Discharge Mode :Rough/Skim Cut



### Technical Specifications

| Models                     | Smartcut 4030 NXG | Smartcut 5035 NXG | Smartcut 6040 NXG | Smartcut 8050 NXG |
|----------------------------|-------------------|-------------------|-------------------|-------------------|
| X,Y Axis Travel (mm)       | 400 x 300         | 500 x 350         | 600 x 400         | 800 x 500         |
| Work Table Size (WxD mm)   | 620 x 430         | 750 x 500         | 880 x 560         | 1080 x 675        |
| Job Admit (mm)             | 300               | 300               | 300               | 500               |
| Max. Workpiece Weight (Kg) | 300               | 600               | 900               | 1500              |
| Max Taper Angle (Deg/mm)   | * +/- 6/100       | * +/- 10/100      | * +/- 10/100      | * +/- 10/100      |
| X,Y LM Guide               | YES               | YES               | YES               | YES               |